



EMERY GLIDETM TECHNICAL SPECIFICATIONS

TESTS AND APPROVALS



Markers embedded for visibility and quidance



The Emery Glide[™] (MR Wire guidewire) is a sterile, disposable guide wire for the introduction and/or placement of diagnostic or interventional devices. Emery Glide[™] is constructed from a high strength core composite of glass fibers and polymers, protected by a high-strength aramid fiber mantle and covered with a PTFE extrusion. The hydrophobic extrusion reduces intravascular friction in devices such as catheters. The distal tip of Emery Glide[™] is marked with discrete ring markers for MRI and X-Ray visibility and comes in different configurations such as straight and angled. Emery Glide[™] is supplied sterile and non-pyrogenic. Emery Glide[™] diameter is 0.035″ (0.89 mm) and is labeled as a MR conditional product according to ASTM F2182, F2052, F2053 and F2213 standards.

| Product number | | CV-G-35180S CV-G-35180A |
|--------------------------|---|--|
| Diameter | > | 0.89 mm (0.035 inch) |
| Length | > | 180 cm (adjustable on demand) |
| Tip shape | > | Straight or Angled |
| Tip length | > | 40 mm (1 37/64 inch) |
| Tip material | > | PTFE |
| Core-shaft-tip | > | One body |
| Core material | > | Fiber-reinforced composite |
| Outer sleeve | > | PTFE |
| MRI and X-ray visibility | > | Straight tip - Passive markers at discrete positions 0, 2 and 4 cm from tip Angled tip - Passive markers at discrete positions 0, 2 and 4 cm from tip |
| Marker material | > | Different nanoparticles embedded in coating |
| MRI labelling | > | MR Conditional |



The symbol is accompanied by a date to indicate that the device may not be used after the end of the year, month or day shown.

| Symbol | Denotation |
|-------------|---|
| <u>+</u> | Guidewire diameter |
| L: ←→ | Total length |
| REF | Catalogue number |
| | Do not use with a metal entry needle |
| | Manufacturer |
| | Date of manufacture |
| \square | Use by date 1 |
| LOT | Batch code |
| STERILE EO | Sterilized using ethylene oxide |
| Ť | Keep dry |
| * | Keep away from sunlight |
| | Do not use if package is damaged |
| | Do not re-use |
| CTENATO | Do not resterilize |
| \triangle | Caution |
| > | Non-pyrogenic |
| Rx only | Caution: Federal law restrcts this device to sale by or on the order of a (licensed) health practitioner. |
| MR | MR Conditional 1.5T or 3.0T |